



# LOOP

SOLO LUCE DIRETTA  
ONLY DIRECT LIGHT




**2129/S50-1**  
W 33 - Vdc 24  
Lm 1.650  
M 2.700°K - C 3.000°K  
W 4.000°K  
H 40 mm  
H MAX 1.700 mm  
Ø 500 mm


+



**2129/R1-60** O/OR  
W 60 - Vac 230  
H 45 mm  
L 360x145 mm  
DIMMERABILE / DIMMABLE  
**2129/R1-60 - D4**  
Taglio di fase / Phase Cut  
**2129/R1-60 - D6**  
1-10V - DALI - PUSH - Bluetooth  
**2129/R1-60 - D7**  
ZigBee  
**2129/R1-60 - D8**  
CASAMBI




**2129/R220-60**  
W 60 - Vac 230  
H 45 mm  
Ø 280 mm + Ø 220 mm  
DIMMERABILE / DIMMABLE  
**2129/R220-60 - D4**  
Taglio di fase / Phase Cut  
**2129/R220-60 - D6**  
1-10V - DALI - PUSH - Bluetooth  
**2129/R220-60 - D7**  
ZigBee  
**2129/R220-60 - D8**  
CASAMBI




**2129/S60-1**  
W 39 - Vdc 24  
Lm 1.850  
M 2.700°K - C 3.000°K  
W 4.000°K  
H 40 mm  
H MAX 1.700 mm  
Ø 600 mm

+



**2129/R1-60** O/OR  
W 60 - Vac 230  
H 45 mm  
L 360x145 mm  
DIMMERABILE / DIMMABLE  
**2129/R1-60 - D4**  
Taglio di fase / Phase Cut  
**2129/R1-60 - D6**  
1-10V - DALI - PUSH - Bluetooth  
**2129/R1-60 - D7**  
ZigBee  
**2129/R1-60 - D8**  
CASAMBI



**2129/R220-60**  
W 60 - Vac 230  
H 45 mm  
Ø 280 mm + Ø 220 mm  
DIMMERABILE / DIMMABLE  
**2129/R220-60 - D4**  
Taglio di fase / Phase Cut  
**2129/R220-60 - D6**  
1-10V - DALI - PUSH - Bluetooth  
**2129/R220-60 - D7**  
ZigBee  
**2129/R220-60 - D8**  
CASAMBI

10 Bianco White  
13 Foglia Argento Silver Leaf  
14 Foglia Oro Gold Leaf  
15 Grigio Grey  
19 Nero Black  
20 Corten Corten



21 Grigio tortora Dove grey  
22 Foglia rame Copper leaf  
23 Ruggine Rust  
24 Ferro Iron  
28 Oro Gold  
29 Alluminio Spaz. Brushed Alum.



19 Nero Black  
24 Ferro Iron  
10 Bianco White  
14 Foglia Oro Gold Leaf  
13 Foglia Argento Silver Leaf  
22 Foglia rame Copper leaf



CRI > 80

DIMMERABILE / DIMMABLE  
Vai a pagina / Go to page 138

DIFFUSORE / DIFFUSER  
Silicone opalino  
Opaline-finish Silicone



LOOP

2129/S50-S75