




## LOOP

SOLO LUCE DIRETTA  
ONLY DIRECT LIGHT



### 2129/TR120

W 81 - Vdc 24

Lm 3.900

M 2.700°K

C 3.000°K - W 4.000°K

H 40 mm

Ø 1200 mm

ON/OFF

AL. 100-24

DIMMERABILE / DIMMABLE

AL.100-24 - D4

Taglio di fase / Phase Cut

AL.100-24 - D6


1-10V - DALI - PUSH - Bluetooth

AL.100-24 - D7

ZigBee

AL.100-24 - D8

CASAMBI



### 2129/TR150

W 97 - Vdc 24

Lm 4.600

M 2.700°K

C 3.000°K - W 4.000°K

H 40 mm

Ø 1500 mm

ON/OFF

AL. 100-24

DIMMERABILE / DIMMABLE

AL.100-24 - D4

Taglio di fase / Phase Cut

AL.100-24 - D6

1-10V - DALI - PUSH - Bluetooth

AL.100-24 - D7

ZigBee

AL.100-24 - D8

CASAMBI

CRI > 80

DIMMERABILE / DIMMABLE

Vai a pagina / Go to page 138

DIFFUSORE / DIFFUSER

Silicone opalino  
Opaline-finish Silicone

10

Bianco  
White



13

Foglia Argento  
Silver Leaf



14

Foglia Oro  
Gold Leaf



15

Grigio  
Grey



19

Nero  
Black



20

Corten  
Corten



21

Grigio tortora  
Dove grey



22

Foglia rame  
Copper leaf



23

Ruggine  
Rust



24

Ferro  
Iron



28

Oro  
Gold



29

Alluminio Spaz.  
Brushed Alum.



19

Nero  
Black



24

Ferro  
Iron



10

Bianco  
White



14

Foglia Oro  
Gold Leaf



13

Foglia Argento  
Silver Leaf



22

Foglia rame  
Copper leaf

