



## ROUND


CRI > 80

**DIMMERABILE / DIMMABLE**

Vai a pagina / Go to page 138

**DIFFUSORE / DIFFUSER**

Silicone opalino  
Opaline-finish Silicone



**2131/TR60**

W 48 - Vdc 24

Lm 2.450

M 2.700°K

C 3.000°K - W 4.000°K

L 600 mm

H 40 mm

ON/OFF

AL. 60-24

**DIMMERABILE / DIMMABLE**

AL.60-24 - D4

Taglio di fase / Phase Cut

AL.60-24 - D6


1-10V - DALI - PUSH - Bluetooth

AL.60-24 - D7

ZigBee

AL.60-24 - D8

CASAMBI



**2131/TR80**

W 66 - Vdc 24

Lm 3.100

M 2.700°K

C 3.000°K - W 4.000°K

L 800 mm

H 40 mm

ON/OFF

AL. 100-24

**DIMMERABILE / DIMMABLE**

AL.100-24 - D4

Taglio di fase / Phase Cut

AL.100-24 - D6

1-10V - DALI - PUSH - Bluetooth

AL.100-24 - D7

ZigBee

AL.100-24 - D8

CASAMBI

19  
Nero  
Black

/

14  
Foglia Oro  
Gold Leaf



24  
Ferro  
Iron

/

13  
Foglia Argento  
Silver Leaf



10  
Bianco  
White

/

22  
Foglia rame  
Copper leaf



10  
Bianco  
White



13  
Foglia Argento  
Silver Leaf



14  
Foglia Oro  
Gold Leaf



19  
Nero  
Black



20  
Corten  
Corten



21  
Grigio tortora  
Dove grey



23  
Ruggine  
Rust



24  
Ferro  
Iron



28  
Oro  
Gold

